



Semi-permeable high-performance construction tape for primer-free application on sheathing substrates

SIGA Wigluv is a tenaciously sticky, low profile, acrylic sealing tape. Constructed of a special vapor-permeable polyolefin (PO) film, reinforcing mesh, and pressure sensitive glue, SIGA Wigluv has been successfully used on mid wall air barrier approaches allowing builders to reach their specific air-tightness goals. Recommended for exterior insulation approaches with regular moisture loads.

CHARACTERISTICS

Available widths	2.4" x 131' 4" x 82'
Thickness	14 mils
Water vapor transmission	1.7 US perms
Max UV exposure	12 months

- ✓ high adhesive strength at high and low temperatures.
- ✓ semi-permeable (1.7 US perms) material allows damp substrates to dry out.
- ✓ UV stable up to 12 months.



INSTALLATION INSTRUCTIONS



- Clean substrate from dust and excess moisture, make sure nails are driven flush



- Apply Wigluv 60 along sheathing joints while ensuring a centered application



- Ensure at least 1" adhesion on each side of the sheathing. For wider joints and corner details use Wigluv 100.



- Apply pressure in order to activate the acrylic glue.



- How it should look

All SIGA products are backed by a 10-Year Limited Warranty. Refer to [siga.swiss](https://www.siga.swiss) for complete details. We want you to maximize SIGA's performance potential on your project. Contact one of our Application Advisors for support, from architectural detail review to jobsite training for installers.